

WELDED PIPE

Standard	ERW Pipe	SSAW Pipe	LSAW Pipe	Hollow Sections	Galvanized Pipe
API	5L, 5CT	5L	5L(psl-1/psl-2),2B		
GB	9711.1 9711.2	9711.1 9711.2	9711.1 9711.2	6728	3091
ASTM	ASTMA53	ASTMA53	A671,A672	ASTMA500	ASTMA53
BS					1387

GALVANIZED PIPE

HIGH-FREQUENCY WELDED

- 1)Outer Diamete: 1/2" to 46"
- 2)Wall thickness: 0.6mm-16mm
- 3)Length: Max. 12 meters
- 4)Standard: GB, ANSI,ASME,ASTM, JIS,DIN,BS,EN
- 5)Steel Grade: Q195/Q215/Q235/Q345/10#/20#/ASTMA106 GRB
- 6)Packaging: Plastic Cap, In bundle.
- 7)Zinc content: 170-550g Per M²
- 8)Applications: petroleum, power,gas metallurgy, papermaking, chemical, medical equipment, aviation, boiler heat, exchanger, shipbuilding, construction, etc.

Type	Galvanized steel pipe/ hot dipped galvanized steel pipe/GI pipe
Thickness	0.6-16 mm
Outer diameter	19-457mm
Length	Max 16meters
Standard	BS, ASTM , ASME , EN , DIN ,GB, JIS
Material	Q195 , Q215 ,Q235 , Q345
Application	Petroleum, power,gas metallurgy, papermaking, chemical, medical equipment, aviation, boiler heat, exchanger, shipbuilding, construction, etc.
Package	Standard exporting package
Delivery time	10-15 days after your deposit
Quality	Superior quality

● British Standard Welded Steel Pipe

Thickness Class	Normal Size		Outside Diameter		Wall Thickness	Calculated Weight (Plain End)		Hexagon Packing
	mm	in.	max mm	min mm		Kg/m	Kg/6m	
			D	D	t			
Class A (Light)	15	1/2"	21.4	21.0	2.0	0.947	5.68	91
	20	3/4"	26.9	26.4	2.3	1.38	8.28	91
	25	1"	33.8	33.2	2.6	1.98	11.88	91
	32	1-1/4"	42.5	41.9	2.6	2.54	15.24	44
	40	1-1/2"	48.4	47.8	2.9	3.23	19.38	44
	50	2"	60.2	59.6	2.9	4.08	24.48	44
	65	2-1/2"	76	75.2	3.2	5.71	34.26	19
	80	3"	88.7	87.9	3.2	6.72	40.32	19
Class B (Medium)	100	4"	113.9	113.0	3.6	9.75	58.50	10
	15	1/2"	21.7	21.1	2.6	1.21	7.26	91
	20	3/4"	27.2	26.6	2.6	1.56	9.36	91
	25	1"	34.2	33.4	3.2	2.41	14.46	91
	32	1-1/4"	42.9	42.1	3.2	3.10	18.60	44
	40	1-1/2"	48.8	48.0	3.2	3.57	21.42	44
	50	2"	60.8	59.8	3.6	5.03	30.18	44
	65	2-1/2"	76.6	75.4	3.6	6.43	38.58	19
Class C (Heavy)	80	3"	89.5	88.1	4.0	8.37	50.22	19
	100	4"	114.9	113.3	4.5	12.2	73.20	10
	15	1/2"	21.7	21.1	3.2	1.44	8.48	91
	20	3/4"	27.2	26.6	3.2	1.87	11.22	91
	25	1"	34.2	33.4	4.0	2.94	17.64	91
	32	1-1/4"	42.9	42.1	4.0	3.80	22.80	44
	40	1-1/2"	48.8	48.0	4.0	4.38	26.28	44
	50	2"	60.8	59.8	4.5	6.19	37.14	44
65	2-1/2"	76.6	75.4	4.5	7.93	47.58	19	
80	3"	89.5	88.1	5.0	10.30	61.80	19	
100	4"	114.9	113.3	5.4	14.50	87.00	10	

Pnc.pipetech.doc/abc

PRODUCT DISPLAY

